

WizSense 8MP outdoor IP camera



- WizSense IP Camera
- 8MP@20ips, Smart H.265+
- ICR, 0.009/0.0009 lux, Smart IR 30m
- 2.8mm fixed lens
- WDR 120dB, 3D-DNR, 4 ROI
- Perimeter protection
- Built-in microphone
- MicroSD slot, RJ45, Onvif, IP67, 3AXIS, PoE.



Reference / Model	IPC-B8FN / IPC-B8FN
1/2.7" 8-megapixel CMOS sensor	
Compression Formats: Smart H.265+, Smart H.264+, H.265, H.264, MJPEG	
Digital resolution: 8MP (3840x2160), 6MP (3072x2048), 5MP (3072x1728, 2880x1620), 4MP (2688x1520), 3MP (2048x1536, 2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)	
Stream 1: 8MP (1~20 fps), 4MP (1~25/30 fps)	
Stream 2: D1 (1~25/30 fps)	
Day/night mode with removable mechanical filter	
Smart IR: 1 IR led, 30 meters range	
0.009 lux F2.0 (color), 0.0009 lux F2.0 (B/W), 0 lux IR On	
2.8 mm fixed optics	
Angle of view: 106°(H), 56°(V), 125°(D)	
Imaging modes: BLC, HLC, WDR 120dB, 3D-NR, Mirror.	
White balance with 6 modes	

WizSense 8MP outdoor IP camera

Reference / Model	IPC-B8FN / IPC-B8FN
	Automatic and manual gain control
	Supports 4-zone videosensor, 4 regions of interest (ROI) and 4-zone privacy masking
	Perimeter protection with cross-line detection and intrusion detection (both modes support person/vehicle classification)
	Built-in microphone
	MicroSD card slot up to 256GB (not included)
	Network interface: RJ45 (10/100 Base-T)
	Network Protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour
	ONVIF (Profile S/G/T), CGI, P2P, Milestone, SDK and API support
	Up to 20 users
	Remote viewing via IE, Chrome and Firefox browsers
	Smart PSS, DSS, DMSS management software
	Compatible with IOS and Android mobile devices
	Power supply: 12V DC / PoE (802.3af)
	Maximum power consumption: 4.5W (12V) / 5.4W (PoE)
	Storage temperature from -40°C ~ +60°C
	Operating temperature: -40°C ~ +60°C (-40°C ~ +60°C)
	Relative humidity: <95%.
	IP67 degree of protection
	Metal housing
	Dimensions: 70 (W) x 70 (H) x 166.2 mm
	Gross weight: 590 g
	Net weight: 480 g
	3AXIS: 0°~360°(PAN), 0°~90°(TILT), 0°~360°(Rotation)