

IPC-D4E

IPC-D4E

OEM

DAHUA IP DOME 4MP WITH SMART IR 30M



- Dahua IP dome camera with Smart IR 40 m vandal-resistant for outdoor use
- CMOS 1/3" 4MP
- Dual-stream
- H.265, H.264, MJPEG formats
- Resolution up to 4MP at 25ips
- ICR filter
- 0.03 lux F2.0
- 2.8 mm (93°) fixed optics
- OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, 4 ROI zones, mirror, video sensor and privacy masks
- Onvif, CGI, P2P
- IP67, IK10
- 3AXIS
- 12V DC
- Supports PoE



Reference / Model	IPC-D4E / IPC-D4E
Specifications	

DAHUA IP DOME 4MP WITH SMART IR 30M

Reference / Model

IPC-D4E / IPC-D4E

4-megapixel 1/1.3" CMOS image sensor
Resolution: 4MP (2688x1520), 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)
Stream 1: 4MP (1~25 ips)
Stream 2: D1 (1~20 fps)
Day/Night mode with removable mechanical filter (ICR)
0.03 lux F2.0
Smart IR: 3 leds, up to 30 metres
H.265, H.264 and MJPEG video compression
2.8 mm fixed optics
Angle of view: 93°(H), 53°(V), 111°(D)
Picture modes: BLC, HLC, WDR 120dB, 3D-DNR, Mirroring.
White balance with 6 modes
Automatic and manual gain control
Supports 4-zone videosensor, 4 regions of interest (ROI) and 4-zone privacy mask
Network interface: RJ45 (10/100 Base-T)
Network Protocols: HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, QoS, UPnP, NTP, RTMP, Multicast, HTTPS, SFTP, 802.1x, ICMP, IGMP
Remote viewing with browsers (IE, Chrome, Firefox) and IOS and Android smartphones
Interoperability: ONVIF S/G/T, CGI, Milestone, Genetec, P2P
Power supply: 12V DC
Power consumption: <5.5W
Supports PoE (802.3 af)
Storage Temperature: -40°C ~ +60°C
Operating conditions: -40°C ~ +60°C, <95% relative humidity
IP67 degree of protection
Vandal-resistant IK10
Metal housing
Dimensions: Ø109.9 x 81 (H) mm
Weight: 350 g
3AXIS: 0°~355°(PAN), 0°~65°(TILT), 0°~355°(Rotation)
Power supply not included