

# IPC-T4ZG2

IPC-T4ZG2

OEM

## 4MP IP Dome, 2.8~12mm, IR 50m, IP67



- IP dome 4MP@20ips, H.265+/H.264+
- ICR, 0.03 lux, Smart IR 50m
- 2.8~12mm motorized optics
- WDR 120dB, 3D-NR, 4 ROIs
- SD slot, RJ45, Onvif, IP67, 3AXIS, PoE.



Reference / Model

IPC-T4ZG2 / IPC-T4ZG2

Specifications

**4MP IP Dome, 2.8~12mm, IR 50m, IP67****Reference / Model****IPC-T4ZG2 / IPC-T4ZG2**

1/3" 4 Megapixel CMOS Image Sensor  
Resolution: 4MP (2688x1520), 3.6MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)  
Video compression H.265+, H.264+, H.265, H.264 and MJPEG  
Stream 1: 4MP (1~20fps), 3.6MP (1~25fps)  
Stream 2: D1 (1~25fps)  
Day/night mode with removable mechanical filter (ICR)  
0.03 lux F1.7 / 0 lux IR on  
Smart IR: 2 leds, up to 50 meters  
2.8~12mm motorized optics  
View Angle: 98°~31°(H), 55°~18°(V), 116°~36°(D)  
Image modes: BLC, HLC, WDR 120dB, 3D-NR, Mirror  
White balance with 6 modes  
Automatic and manual gain control  
Supports 4-zone video sensor, 4 regions of interest (ROI) and 4-zone privacy mask  
MicroSD card slot up to 256GB (card not included)  
Network interface: RJ45 (10/100 Base-T)  
Network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour  
Remote viewing with browsers (IE, Chrome, Firefox) and IOS and Android smartphone  
Interoperability: ONVIF S/G/T, CGI, Milestone, Genetec, P2P  
Power: 12V DC / PoE (802.3af)  
Consumption: <6.9W  
Storage temperature: -30°C ~ +60°C  
Operating conditions: -40°C ~ +60°C, relative humidity <95%  
Degree of protection IP67  
metal casing  
Dimensions: Ø122 x 108.3 (H) mm  
Weight: 690g  
3AXIS: 0°~355°(PAN), 0°~78°(TILT), 0°~360°(Rotation)