

SAM-4215R

IPC-T6F

OEM

Outdoor 6MP IP dome

6MP



 IP67

STARLIGHT

 120 dB WDR

H.265+







- 6MP@25ips IP dome, H.265+/H.264+
- ICR, 0.008 lux, Smart IR 30m
- 2.8mm fixed lens
- WDR 120dB, 3D-NR, 4 ROIs
- IVS intelligence
- Includes microphone
- MicroSD slot, RJ45, Onvif, IP67, 3AXIS, PoE



| Reference / Model | SAM-4215R / IPC-T6F |
|-------------------|---------------------|
| specs             |                     |

## Outdoor 6MP IP dome

## Reference / Model

## SAM-4215R / IPC-T6F

1/2.7" 6 megapixel CMOS sensor  
Compression formats: H.265+, H.265, H.264+, H.264, MJPEG  
Digital resolution: 6MP (3072x2048), 4MP (2688x1520), 3MP (2048x1536), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)  
Stream 1: 6MP (1~25fps), 4MP (1~25/30fps)  
Stream 2: D1 (1~25fps)  
Day/night mode with removable mechanical filter  
Smart IR: 2 leds, 30 meters  
0.008lux F1.6  
2.8mm fixed lens  
View Angle: 103°(H), 71°(V), 132°(D)  
Image modes: BLC, HLC, WDR 120dB, 3D-NR, Mirror  
White balance with 6 modes  
Automatic and manual gain control  
Supports 4-zone video sensor, 4 regions of interest (ROI) and 4-zone privacy mask  
Intelligent detection (IVS): line crossing detection, intrusion detection  
Includes microphone  
MicroSD card slot up to 256GB (not included)  
Network interface: RJ45 (10/100 Base-T)  
Network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour  
Compatible with ONVIF (Profile S/G/T), CGI, P2P, Milestone, Genetec  
Up to 20 users  
Remote viewing via IE, Chrome, Firefox browsers  
Compatible with IOS and Android mobile devices  
Power: 12V DC / PoE (802.3af)  
Consumption: 7.2W  
Storage temperature -40°C ~ +60°C  
Operating temperature -40°C ~ +60°C  
Relative humidity: <95%  
Degree of protection IP67  
metal casing  
Dimensions: Ø121.9 (H) x 99.1mm  
Weight: 480g  
3AXIS: 0°~360°(PAN), 0°~78°(TILT), 0°~360°(Rotation)