

5MP outdoor IP dome



- IP Dome 5MP@20ips, Smart H.265+
- ICR, 0.005/0.0005 lux, Smart IR 30m
- 2.8mm fixed optical
- WDR 120dB, 3D-NR, 4 ROI
- Perimeter protection
- SMD Plus
- Built-in microphone
- MicroSD slot, RJ45, Onvif, IP67, IK10, 3AXIS, PoE



Reference / Model	SAM-4883 / SAM-4883
5-megapixel 1/2.7" CMOS sensor	
Compression formats: Smart H.265+, Smart H.264+, H.265, H.264, MJPEG	
Digital resolution: 5MP (2592x1944), 4MP (2688x1520), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)	
Stream 1: 5MP (1~20 fps), 4MP (1~25/30 fps)	
Stream 2: D1 (1~25/30 fps)	
Day/Night mode with removable mechanical filter	
Smart IR: 3 IR leds, 30 meters	
0.005 lux F1.6 (color), 0.0005 lux F1.6 (B/W), 0 lux IR on	
2.8 mm fixed optics	
Angle of view: 97°(H), 71°(V), 129°(D)	
Imaging modes: BLC, HLC, WDR 120dB, 3D-NR, Mirror.	
White balance with 6 modes	

5MP outdoor IP dome

Reference / Model	SAM-4883 / SAM-4883
Automatic and manual gain control	
Supports 4-zone videosensor, 4 regions of interest (ROI) and 4-zone privacy masking	
Perimeter protection with cross-line detection and intrusion detection (both modes support human/vehicle classification)	
SMD Plus	
Built-in microphone	
MicroSD card slot up to 256GB (not included)	
Network interface: RJ45 (10/100 Base-T)	
Network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP	
ONVIF (Profile S/G/T), CGI, P2P, Milestone, Genetec, SDK and API support	
Up to 20 users	
Remote viewing via IE, Chrome, Firefox browsers	
Management software	
Compatible with IOS and Android mobile devices	
Power supply: 12V DC / PoE (802.3af)	
Maximum power consumption: 6W (12V) / 7.2W (PoE)	
Storage temperature from -40°C ~ +60°C	
Operating temperature: -40°C ~ +60°C (-40°C ~ +60°C)	
Relative humidity: <95%.	
IP67 degree of protection	
Vandal protection IK10	
Metal housing	
Dimensions: Ø109.9 x 81 (H) mm	
Weight: 351 g	
3AXIS: 0°~355°(PAN), 0°~65°(TILT), 0°~355°(Rotation)	