

WizSense 5MP IP Dome for outdoor use**5MP****IP67****STARLIGHT****120 dB
WDR****H.265+****P2P****Wiz Sense****SMD**
Smart Motion Detection

- WizSense 5MP@20ips IP Dome, Smart H.265+
- ICR, 0.005/0.0005 lux, Smart IR 40m
- 2.7~13.5mm motorized optics
- WDR 120dB, 3D-NR, 4 ROI
- Perimeter protection
- Built-in microphone
- MicroSD slot, RJ45, Onvif, IP67, 3AXIS, PoE.

**Reference / Model****SAM-4889 / SAM-4889**

5-megapixel 1/2.7" CMOS sensor

Compression Formats: Smart H.265+, Smart H.264+, H.265, H.264, MJPEG

Digital resolution: 5MP (2592x1944), 4MP (2688x1520), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)

Stream 1: 5MP (1~20 ips), 4MP (1~25/30 ips)

Stream 2: D1 (1~25/30 fps)

Day/Night mode with removable mechanical filter

Smart IR: 2 IR LEDs, 40 meters range

0.005 lux F1.5 (color), 0.0005 lux F1.5 (B/W), 0 lux IR On

2.7~13.5 mm motorized optics

Angle of view: 100°~30°(H), 72°~23°(V), 134°~38°(D)

Imaging modes: BLC, HLC, WDR 120dB, 3D-NR, Mirror.

White balance with 6 modes

WizSense 5MP IP Dome for outdoor use

Reference / Model	SAM-4889 / SAM-4889
Automatic and manual gain control	
Supports 4-zone videosensor, 4 regions of interest (ROI) and 4-zone privacy masking	
Perimeter protection with cross-line detection and intrusion detection (both modes support human/vehicle classification)	
SMD Plus	
Built-in microphone	
MicroSD card slot up to 256GB (not included)	
Network interface: RJ45 (10/100 Base-T)	
Network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP	
ONVIF (Profile S/G/T), CGI, P2P, Milestone, Genetec, SDK and API support	
Up to 20 users	
Remote viewing via IE, Chrome and Firefox browsers	
Smart PSS, DSS, DMSS management software	
Compatible with IOS and Android mobile devices	
Power supply: 12V DC / PoE (802.3af)	
Consumption: 5.4W (12V) / 6.4W (PoE)	
Storage temperature from -40°C ~ +60°C	
Operating temperature from -30°C ~ +60°C	
Relative humidity: ≤95%.	
IP67 degree of protection	
Metal housing	
Dimensions: Ø122 x 108.3 (H) mm	
Net weight: 685 g	
Gross weight: 828 g	
3AXIS: 0°~360°(PAN), 0°~78°(TILT), 0°~360°(Rotation)	