

# SAM-4892

SAM-4892

OEM

## 2MP outdoor IP camera



- IP Camera 2MP@25/30ips, H.265+/H.264+
- ICR, 0.005/0.0005 lux, Smart IR 30m
- 2.8mm fixed optical
- BLC, HLC, digital WDR, 3D-NR, 4 ROI
- IVS intelligence
- MicroSD slot, RJ45, Onvif, IP67, 3AXIS, PoE.



### Reference / Model

SAM-4892 / SAM-4892

2 megapixel 1/2.8" CMOS image sensor

Resolution: 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)

Smart H.265+, Smart H.264+, H.265, H.264 and MJPEG video compression

Stream 1: 1080P (1~25 fps)

Stream 2: D1 (1~25 fps)

Day/night mode with removable mechanical filter (ICR)

0.005 lux F1.6 (color) / 0.0005 lux F1.6 (B/W) / 0 lux IR on

Smart IR: 1 led, up to 30 meters

2.8 mm fixed optics

Angle of view: 107°(H), 56°(V), 127°(D)

Imaging modes: BLC, HLC, digital WDR, 3D-NR, Mirror.

White balance with 6 modes

Automatic and manual gain control

**2MP outdoor IP camera**

Reference / Model	SAM-4892 / SAM-4892
	Supports 4-zone videosensor, 4 regions of interest (ROI) and 4-zone privacy mask
	Intelligent Video Sensing (IVS): Intrusion Detection, Cross Line Detection
	MicroSD card slot up to 256GB (card not included)
	Network interface: RJ45 (10/100 Base-T)
	Network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour
	Remote viewing with browsers (IE, Chrome, Firefox) and IOS and Android smartphones
	Smart PSS, DSS and DMSS management software
	Interoperability: ONVIF S/G/T, CGI, Milestone, Genetec, P2P
	Power supply: 12V DC / PoE (802.3at)
	Consumption: 3.9W (12V) / 4.7W (PoE)
	Storage temperature: -40°C ~ +60°C (-40°C ~ +60°C)
	Operating conditions: -40°C ~ +60°C, relative humidity <95%.
	IP67 protection rating
	Metal housing
	Dimensions: Ø70 x 166.2 (H) mm
	Weight: 480 g
	3AXIS: 0°~360°(PAN), 0°~90°(TILT), 0°~360°(Rotation)
	Feeder not included