

SAM-4898

SAM-4898

OEM

Outdoor 4MP IP camera



- WizSense IP Camera 4MP@25/30ips, Smart H.265+
- ICR, 0.005/0.0005 lux, Smart IR 50m
- 2.8mm fixed optics
- WDR 120dB, 3D-DNR, 4 ROI
- Perimeter protection
- Built-in microphone
- MicroSD slot, RJ45, Onvif, IP67, 3AXIS, PoE.



Reference / Model

SAM-4898 / SAM-4898

4 megapixel 1/3" CMOS sensor

Compression formats: Smart H.265+, Smart H.264+, H.265, H.264, MJPEG

Digital resolution: 4MP (2688x1520), 4MP (2560x1440), 3MP (2048x1536), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)

Stream 1: 4MP (1~25/30 ips)

Stream 2: D1 (1~25/30 fps)

Stream 3: 1080P (1~25/30 fps)

Day/night mode with removable mechanical filter

Smart IR: 1 IR led, 50 meters range

0.005 lux F1.4 (color), 0.0005 lux F1.4 (B/W), 0 lux IR On

2.8 mm fixed optics

Angle of view: 107°(H), 56°(V), 127°(D)

Imaging modes: BLC, HLC, WDR 120dB, 3D-NR, AFSA, Mirror, Defog

Outdoor 4MP IP camera

Reference / Model	SAM-4898 / SAM-4898
White balance with 6 modes	
Automatic gain control	
Supports 4-zone videosensor, 4 regions of interest (ROI) and 4-zone privacy mask	
Perimeter protection with cross-line detection and intrusion detection (both modes support person/vehicle classification)	
Built-in microphone	
MicroSD card slot up to 256GB (not included)	
Network interface: RJ45 (10/100 Base-T)	
Network protocols: IPv4, IPv6, HTTP;TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP	
ONVIF (Profile S/G/T), CGI, P2P, Milestone, Genetec, SDK and API support	
Up to 20 users	
Remote viewing via IE11, Chrome and Firefox browsers	
Smart PSS, DSS, DMSS management software	
Compatible with IOS and Android mobile devices	
Power supply: 12V DC / PoE (802.3af)	
Maximum power consumption: 5.9W (12V) / 7.2W (PoE)	
Storage temperature from -40°C ~ +60°C	
Operating temperature: -40°C ~ +60°C (-40°C ~ +60°C)	
Relative humidity: <95%.	
IP67 protection rating	
Metal housing	
Dimensions: 70,5 (W) x 66,4 (H) x 192,7 mm	
Weight: 590 g	
3AXIS: 0°~360°(PAN), 0°~90°(TILT), 0°~360°(Rotation)	